

Python For Data Science Cheat Sheet

Bokeh

Learn Bokeh [Interactively](#) at www.DataCamp.com, taught by Bryan Van de Ven, core contributor




Plotting With Bokeh

The Python interactive visualization library **Bokeh** enables high-performance visual presentation of large datasets in modern web browsers.



Bokeh's mid-level general purpose `bokeh.plotting` interface is centered around two main components: data and glyphs.



The basic steps to creating plots with the `bokeh.plotting` interface are:

1. Prepare some data:
Python lists, NumPy arrays, Pandas DataFrames and other sequences of values
2. Create a new plot
3. Add renderers for your data, with visual customizations
4. Specify where to generate the output
5. Show or save the results

```
>>> from bokeh.plotting import figure
>>> from bokeh.io import output_file, show
>>> x = [1, 2, 3, 4, 5]           Step 1
>>> y = [6, 7, 2, 4, 5]
>>> p = figure(title="simple line example",      Step 2
              x_axis_label='x',
              y_axis_label='y')
>>> p.line(x, y, legend="Temp.", line_width=2)    Step 3
>>> output_file("lines.html")                  Step 4
>>> show(p)                                    Step 5
```

1 Data

Also see Lists, NumPy & Pandas

Under the hood, your data is converted to Column Data Sources. You can also do this manually:

```
>>> import numpy as np
>>> import pandas as pd
>>> df = pd.DataFrame(np.array([[33.9, 4, 65, 'US'],
                               [32.4, 4, 66, 'Asia'],
                               [21.4, 4, 109, 'Europe']]),
                     columns=['mpg', 'cyl', 'hp', 'origin'],
                     index=['Toyota', 'Fiat', 'Volvo'])

>>> from bokeh.models import ColumnDataSource
>>> cds_df = ColumnDataSource(df)
```

2 Plotting

```
>>> from bokeh.plotting import figure
>>> p1 = figure(plot_width=300, tools='pan,box_zoom')
>>> p2 = figure(plot_width=300, plot_height=300,
               x_range=(0, 8), y_range=(0, 8))
>>> p3 = figure()
```

3 Renderers & Visual Customizations

Glyphs

Scatter Markers

```
>>> p1.circle(np.array([1,2,3]), np.array([3,2,1]),
             fill_color='white')
>>> p2.square(np.array([1.5,3.5,5.5]), [1,4,3],
             color='blue', size=1)
```

Line Glyphs

```
>>> p1.line([1,2,3,4], [3,4,5,6], line_width=2)
>>> p2.multi_line(pd.DataFrame([[1,2,3],[5,6,7]]),
                  pd.DataFrame([[3,4,5],[3,2,1]]),
                  color="blue")
```

Rows & Columns Layout

Rows

```
>>> from bokeh.layouts import row
```

```
>>> layout = row(p1,p2,p3)
```

Columns

```
>>> from bokeh.layouts import column
```

```
>>> layout = column(p1,p2,p3)
```

```
>>> layout = row(column(p1,p2), p3)
```

Grid Layout

```
>>> from bokeh.layouts import gridplot
>>> row1 = [p1,p2]
>>> row2 = [p3]
>>> layout = gridplot([[p1,p2],[p3]])
```

Tabbed Layout

```
>>> from bokeh.models.widgets import Panel, Tabs
>>> tab1 = Panel(child=p1, title="tab1")
>>> tab2 = Panel(child=p2, title="tab2")
>>> layout = Tabs(tabs=[tab1, tab2])
```

Legends

Legend Location

Inside Plot Area

```
>>> p.legend.location = 'bottom_left'
```

Outside Plot Area

```
>>> r1 = p2.asterisk(np.array([1,2,3]), np.array([3,2,1]))
>>> r2 = p2.line([1,2,3,4], [3,4,5,6])
>>> legend = Legend(items=[("One", [p1, r1]), ("Two", [r2])], location=(0, -30))
>>> p.add_layout(legend, 'right')
```

Customized Glyphs

Selection and Non-Selection Glyphs

```
>>> p = figure(tools='box_select')
>>> p.circle('mpg', 'cyl', source=cds_df,
             selection_color='red',
             nonselection_alpha=0.1)
```

Hover Glyphs

```
>>> hover = HoverTool(tooltips=None, mode='vline')
>>> p3.add_tools(hover)
```

Colormapping

```
>>> color_mapper = CategoricalColorMapper(
            factors=['US', 'Asia', 'Europe'],
            palette=['blue', 'red', 'green'])
>>> p3.circle('mpg', 'cyl', source=cds_df,
             color=dict(field='origin',
                        transform=color_mapper),
             legend='Origin'))
```

Also see Data

Linked Plots

Linked Axes

```
>>> p2.x_range = p1.x_range
>>> p2.y_range = p1.y_range
```

Linked Brushing

```
>>> p4 = figure(plot_width = 100, tools='box_select,lasso_select')
>>> p4.circle('mpg', 'cyl', source=cds_df)
>>> p5 = figure(plot_width = 200, tools='box_select,lasso_select')
>>> p5.circle('mpg', 'hp', source=cds_df)
>>> layout = row(p4,p5)
```

Legend Orientation

```
>>> p.legend.orientation = "horizontal"
>>> p.legend.orientation = "vertical"
```

Legend Background & Border

```
>>> p.legend.border_line_color = "navy"
>>> p.legend.background_fill_color = "white"
```

4 Output

Output to HTML File

```
>>> from bokeh.io import output_file, show
>>> output_file('my_bar_chart.html', mode='cdn')
```

Notebook Output

```
>>> from bokeh.io import output_notebook, show
>>> output_notebook()
```

Embedding

Standalone HTML

```
>>> from bokeh.embed import file_html
>>> html = file_html(p, CDN, "my_plot")
```

Components

```
>>> from bokeh.embed import components
>>> script, div = components(p)
```

5 Show or Save Your Plots

```
>>> show(p1)
>>> show(layout)
```

```
>>> save(p1)
>>> save(layout)
```

Also see Data

Statistical Charts With Bokeh

Bokeh's high-level `bokeh.charts` interface is ideal for quickly creating statistical charts

Bar Chart

```
>>> from bokeh.charts import Bar
>>> p = Bar(df, stacked=True, palette=['red','blue'])
```

Box Plot

```
>>> from bokeh.charts import BoxPlot
>>> p = BoxPlot(df, values='vals', label='cyl',
                legend='bottom_right')
```

Histogram

```
>>> from bokeh.charts import Histogram
>>> p = Histogram(df, title='Histogram')
```

Scatter Plot

```
>>> from bokeh.charts import Scatter
>>> p = Scatter(df, x='mpg', y ='hp', marker='square',
                xlabel='Miles Per Gallon',
                ylabel='Horsepower')
```

